

TECHNICAL DATA

Model	Venezia 90 frameless	Venezia 130 frameless	u.m.
Heat input max/min	6,3/2,5	10/4	kW
Heat output Nom./Red. Pn	4,85/1,65	7,6/2,67	kW
Exhaust type	C11-C31		
Efficiency level	79	74,7	%
Efficiency class	2		class
NOx	5		class
Consumption G20 Nom./Red.	0,666/0,253	1,057/0,423	m ³ /h
Consumption G31 Nom./Red.	0,489/0,189	0,776/0,310	Kg/h
Press. nom. supply G20/G31	20/37		mbar
Press. nom. nozzles G20/G31	12/36,8	12/36,5	mbar
Press. nom. nozzles G20/G31 Red.	2/6	2/6,2	mbar
Ø burner nozzle G20/G31	2,10/1,25	1,98/1,10	mm
Pilot nozzle	0,35/0,25		code
Power supply (optional)	230VAC / 6VCC		V
Power input	0		W
Gas connection pipe	3/8" - Ø10		Ø mm
Gas valve to burner supply pipe (max length = 1m)	8		Ø mm
Remote control battery (nr. 1)	9V PP3		type
Receiver battery (nr. 4)	1,5V AA		type
Electrical protection	IP20		
Gas category	I 2H - I 3P		
Max flue line lenght (Ø150)	see page 100	see page 100	m
Max flue line lenght (Ø200)	see page 100	see page 100	m

CONTROLS



Basic remote control:

- Off appliance.
- On/Thermostat knob regulation.
- Warning light transmission control



Rem. control with display (optional):

- Room temperature and desired.
- AM/PM time.
- Thermostat knob regulation.
- Manual or timer program.
- Dual timer program: for day and night.